

DECLARATION OF PERFORMANCE

according Annex III of the Regulation (EU) No 305/2011

No. 149/1

1. Unique identification code of the product-type :

EMFIMASTIC PU 25 Bâtiment NG

2. Type, batch or serial number or any other element allowing identification of the construction product as required pursuant to Article 11(4) :

Batch number : see packaging of the product

3. Intended use or uses of the construction product, in accordance with the applicable harmonised technical specification, as foreseen by the manufacturer :

Sealant for non-structural use in joints in buildings for facade elements for exterior and interior applications intended for use in cold climate

EN 15651-1 : F EXT-INT CC

4. Name, registered trade name or registered trade mark and contact address of the manufacturer as required pursuant to Article 11(5) :

EMFI S.A.S.

3, Rue Ettore Bugatti

F - 67500 HAGUENAU

5. Where applicable, name and contact address of the authorised representative whose mandate covers the tasks specified in Article 12(2) :


Not relevant

6. System or systems of assessment and verification of constancy of performance of the construction product as set out in Annex V :

System 3

7. In case of the declaration of performance concerning a construction product covered by a harmonised standard :

The notified body GINGER CEBTP, identification number 0074, performed the type tests and issued a test report.



8. In case of the declaration of performance concerning a construction product for which a European Technical Assessment has been issued :

Not relevant

9. Declared performance

Class : 25 LM
Substrates : Mortar M2 and Aluminium without primer

Essential characteristics	Testing Standards	Performances	Harmonised technical specification
Reaction to fire	EN 13501-1 + A1	Class E	EN 15651-1:2012
Water tightness and air tightness			
Loss of volume	EN ISO 10563	≤ 10 %	
Resistance to flow	EN ISO 7390	≤ 3 mm	
Adhesion / Cohesion determination of tensile properties at maintained extension after immersion in water (23°C)	EN ISO 10590	NF	
Adhesion / Cohesion determination of tensile properties at -30°C	EN ISO 8339 amended	≤ 0,9 MPa	
Adhesion / Cohesion determination of tensile properties at maintained extension at -30°C	EN ISO 8340 amended	NF	
Durability	EN ISO 8340 EN ISO 9047 EN ISO 10590	Compliant	

NF : no failure

10. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9.

This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Signed for and on behalf of the manufacturer by :

Vincent FRAYSSE – Site Manager



Haguenau, 25/04/2014