




A 3M Company

COLLES MASTICS ETANCHEITE COLLES MASTICS ETANCHEITE



## DECLARATION OF PERFORMANCE

according Annex III of the Regulation (EU) No 305/2011

No. 114SL/4

1. Unique identification code of the product-type :

**EMFIMASTIC PU 40 SELF-LEVELING**

2. Type, batch or serial number or any other element allowing identification of the construction product as required pursuant to Article 11(4) :

**Batch number : see packaging of the product**

3. Intended use or uses of the construction product, in accordance with the applicable harmonised technical specification, as foreseen by the manufacturer :

**Sealant for pedestrian walkways for exterior and interior applications  
intended for use in cold climate**

**EN 15651-4 : PW EXT-INT CC**

4. Name, registered trade name or registered trade mark and contact address of the manufacturer as required pursuant to Article 11(5) :

**EMFI S.A.S.**

**3, Rue Ettore Bugatti**

**F - 67500 HAGUENAU**

5. System or systems of assessment and verification of constancy of performance of the construction product as set out in Annex V :

**System 3**

6. In case of the declaration of performance concerning a construction product covered by a harmonised standard :

**The notified body GINGER CEBTP, identification number 0074, performed the type tests  
and issued a test report**




**EMFI S.A.S.**

Société au capital de 3 104 019,60 euros  
SIRET 588 500 256 00106  
RC STRASBOURG 588 500 256 B  
Code APE 2052Z ID CEE : FR 94 588 500 256

3 rue Ettore Bugatti - CS 40030  
F 67501 Haguenau Cedex - FRANCE  
Tel. +33 (0)3 88 90 60 00  
Fax +33 (0)3 88 73 48 38  
E-mail : emfi@emfi.com  
[www.emfi.com](http://www.emfi.com)





7. Declared performance :

**Class : 25 LM**

**Substrate : Mortar M1 with primer**

Essential characteristics	Testing standards	Performances	Harmonised technical specification
Reaction to fire	EN 13501-1 + A1	<b>Class E</b>	EN 15651-4 : 2012
Water tightness and air tightness			
Loss of volume	EN ISO 10563	<b>≤ 10 %</b>	
Tear resistance	EN ISO 8340 amended	<b>Compliant</b>	
Adhesion/cohesion determination of tensile properties at maintained extension after immersion in water (28 days)	EN ISO 10590 amended	<b>Compliant</b>	
Adhesion/cohesion determination of tensile properties at maintained extension after immersion in salt water (28 days)	EN ISO 10590 amended	<b>NF</b>	
Adhesion/cohesion determination of tensile properties at -30 °C	EN ISO 8339 amended	<b>≤ 0,9 MPa</b>	
Adhesion/cohesion determination of tensile properties at maintained extension at -30 °C	EN ISO 8340 amended	<b>NF</b>	
Durability	EN ISO 8340 EN ISO 9047 EN ISO 10590	<b>Compliant</b>	

NF : no failure

8. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 7.

This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Signed for and on behalf of the manufacturer by :

Vincent FRAYSSE – Site Manager



Haguenau, 02/06/2014



**EMFI S.A.S.**

Société au capital de 3 104 019,60 euros  
SIRET 588 500 256 00106  
RC STRASBOURG 588 500 256 B  
Code APE 2052Z ID CEE : FR 94 588 500 256

3 rue Ettore Bugatti - CS 40030  
F 67501 Haguenau Cedex - FRANCE  
Tel. +33 (0)3 88 90 60 00  
Fax +33 (0)3 88 73 48 38  
E-mail : emfi@emfi.com  
[www.emfi.com](http://www.emfi.com)

