



Product code : D0521

HARDENER 521

DESCRIPTION

HARDENER 521 is a hardener used with polyurethane based adhesives.

AREAS OF APPLICATIONS

HARDENER 521 is used to provide a stronger resistance of the bonding to water and heat.

TECHNICAL DATA

Appearance	Diphenylmethane diisocyanate
Color	Dark brown
Viscosity at 20°C	Brookfield LVT 2 / 30 rpm: 250 ± 100 mPa.s
Density at 20°C	1.23 ± 0.02
Cleaner	EMFINET 683 before setting (highly flammable)
Temperature resistance	Read technical data sheet of used adhesive

INSTRUCTIONS FOR USE

Read the technical data sheet of the mix "PU ADHESIVE + HARDENER 521". Well respect the mixing ratio indicated on it.
Mix with recommended adhesive until complete homogenization.

STORAGE AND SHELF LIFE

12 months in closed original packaging stored at a temperature between 5 and 25°C.
After opening, it is necessary to protect the product from humidity.
In cold weather, store the packaging at about 20°C before use.

PACKAGING

5 kg metal cans, 250 kg metal drums and containers.
Contact us for other packaging options.

SAFETY

Read material safety data sheet before use.

The technical data contained herein is based on our present knowledge and experience and we cannot be held liable for any errors, inaccuracies, omissions or editorial failings that result from technological changes or research between the date of issue of this document and the date the product is acquired. Before using the product, the user should carry out any necessary tests in order to ensure that the product is suitable for the intended application. Moreover, all users should contact the seller or the manufacturer of the product for additional technical information concerning its use if they think that the information in their possession needs to be clarified in any way, whether for normal use or a specific application of our product. Our guarantee applies within the context of the statutory regulations and provisions in force, current professional standards and in accordance with the stipulations set out in our general sales conditions. The information detailed in the present technical data sheet is given by way of indication and is not exhaustive. The same applies to any information provided verbally by telephone to any prospective or existing customer.