



Product code : 70059A

DEGREASER 1001

DESCRIPTION

DEGREASER 1001 is a mixture of polysilanes in solution in organic solvents.

AREAS OF APPLICATIONS

DEGREASER 1001 can be used both as a degreaser or an adhesion promoter for polyurethane, hybrid SPUR and MS sealants or silicones.

DEGREASER 1001 can be used in many fields, for example for the surface preparation before application of a primer for glass bonding or on substrates such as HPL, ceramic, fiber cement or aluminium profile and other non-porous surfaces.

TECHNICAL DATA

Color	Transparent colorless liquid
Viscosity	Fluid
Density at 20°C	Approx. 0.80
Application temperature	5 to 35°C
Drying time	Approx. 30 s *

* if the temperature is below 20°C, a longer drying time is recommended.

INSTRUCTIONS FOR USE

Substrate preparation:

The substrates to be treated must be clean, dry and free of dust.

Note: when using solvents, extinguish all sources of ignition and carefully follow the safety and handling instructions given by the manufacturer.

Application:

Shake the bottle before use.

- As a cleaner: apply DEGREASER 1001 on the substrate with a clean, dry and lint-free cloth and wipe as soon as the solvent has evaporated, i.e. 30 to 60 seconds after application.

- As a primer: apply a thin and uniform film of DEGREASER 1001 with a brush or a felt tip applicator. Dip a clean felt tip applicator into the bottle, roll it around the edges of the bottle to squeeze out the excess of product.

Exert a uniform and light pressure, in a single pass ("Wipe On" method), to get a homogenous film.

Close the bottle immediately after use as this product is very sensitive to moisture. If the product gets cloudy, do not use it anymore.

After drying (10 minutes * depending on temperature and moisture conditions), apply sealant within a one-hour deadline following the instructions of its technical datasheet.

* if the temperature is below 20°C, a longer drying time is recommended.

STORAGE AND SHELF LIFE

12 months in closed original packaging stored at a temperature between 5 and 25°C.

1 month after opening in well closed original packaging stored at a temperature between 5 and 25°C.

PACKAGING

30, 250 and 1000 ml aluminum bottles, 25 L cans.

Contact us for other packaging options.

SAFETY

Read material safety data sheet before use.

The technical data contained herein is based on our present knowledge and experience and we cannot be held liable for any errors, inaccuracies, omissions or editorial failings that result from technological changes or research between the date of issue of this document and the date the product is acquired.

Before using the product, the user should carry out any necessary tests in order to ensure that the product is suitable for the intended application. Moreover, all users should contact the seller or the manufacturer of the product for additional technical information concerning its use if they think that the information in their possession needs to be clarified in any way, whether for normal use or a specific application of our product.

Our guarantee applies within the context of the statutory regulations and provisions in force, current professional standards and in accordance with the stipulations set out in our general sales conditions.

The information detailed in the present technical data sheet is given by way of indication and is not exhaustive. The same applies to any information provided verbally by telephone to any prospective or existing customer.