



Product code : 36026A

POLYMASTIC I

DESCRIPTION

POLYMASTIC 1 is an adhesive / sealant based on synthetic elastomers and special solvents that do not attack polystyrene.
POLYMASTIC 1 has a high tack after evaporation of solvents and a good resistance to water.



AREAS OF APPLICATIONS

POLYMASTIC 1 is specially adapted for bonding expanded and extruded polystyrene in slabs and panels, conventional building insulating materials (mineral wools, polyurethane panels), decorative rosettes and cornices, wooden and PVC skirting boards, etc. on most porous and non-porous building substrates.

ADVICE

See also material safety data sheet

TECHNICAL DATA

INSTRUCTIONS FOR USE

Refer to product's technical data sheet.

The technical data contained herein is based on our present knowledge and experience and we cannot be held liable for any errors, inaccuracies, omissions or editorial failings that result from technological changes or research between the date of issue of this document and the date the product is acquired.
Before using the product, the user should carry out any necessary tests in order to ensure that the product is suitable for the intended application. Moreover, all users should contact the seller or the manufacturer of the product for additional technical information concerning its use if they think that the information in their possession needs to be clarified in any way, whether for normal use or a specific application of our product.
Our guarantee applies within the context of the statutory regulations and provisions in force, current professional standards and in accordance with the stipulations set out in our general sales conditions.
The information detailed in the present technical data sheet is given by way of indication and is not exhaustive. The same applies to any information provided verbally by telephone to any prospective or existing customer.