



Product code : 74071

EMFIMASTIC PU 501

DESCRIPTION

EMFIMASTIC PU 501 is a single component polyurethane based elastomeric sealant. It forms a joint of high elasticity and has a good resistance to tear and to weather.



AREAS OF APPLICATIONS

EMFIMASTIC PU 501 is specially adapted for bonding various materials used in the general industry.

It adheres without primer on substrates commonly used, like wood, anodized aluminium, lacquered metal, polyester, concrete, glass.

For difficult materials, including plastics such as PVC, ABS, PMMA, or materials such as bare aluminium, perform preliminary tests to determine whether a surface preparation is necessary.

ADVICE

See also material safety data sheet

TECHNICAL DATA

INSTRUCTIONS FOR USE

Refer to product's technical data sheet.

The technical data contained herein is based on our present knowledge and experience and we cannot be held liable for any errors, inaccuracies, omissions or editorial failings that result from technological changes or research between the date of issue of this document and the date the product is acquired.

Before using the product, the user should carry out any necessary tests in order to ensure that the product is suitable for the intended application. Moreover, all users should contact the seller or the manufacturer of the product for additional technical information concerning its use if they think that the information in their possession needs to be clarified in any way, whether for normal use or a specific application of our product.

Our guarantee applies within the context of the statutory regulations and provisions in force, current professional standards and in accordance with the stipulations set out in our general sales conditions.

The information detailed in the present technical data sheet is given by way of indication and is not exhaustive. The same applies to any information provided verbally by telephone to any prospective or existing customer.