

Product code: 75035E

EMFIMASTIC HIGH POWER

DESCRIPTION

EMFIMASTIC HIGH POWER is a single component high-viscosity elastomeric sealant, based on silane terminated polymer and presenting high immediate bonding properties. After application, it cures under the effect of atmospheric humidity or substrates humidity to form a flexible joint presenting a high resistance to tear.



AREAS OF APPLICATIONS

EMFIMASTIC HIGH POWER can be used in the building and general industries, indoor or outdoor, to bond elements which may be subject to vibrations or deformations. The adhesion is excellent on a wide range of substrates commonly used in the building industry (tiling, glass, wood, PVC, pre-painted aluminium, most of the metals, polystyrene, stone, polyester, concrete, etc.)

However, due to the large variety of substrates and installation conditions, it is necessary to make tests beforehand on difficult materials (particularly on non-ferrous or lacquered metals and plastic substrates like PVC, PMMA or ABS) to determine whether abrasion or the use of a primer may be necessary to improve adhesion.

For further information, contact our technical department.

Not suitable for substrates like PE, PP, Teflon, wallpaper-glass cloth.

Avoid any contact with oils, plasticizers or products like bitumen, asphalt, silicone, etc.

ADVICE

See also material safety data sheet

TECHNICAL DATA

 C 1	
 COLOR	
 COIOI	

INSTRUCTIONS FOR USE

Refer to product's technical data sheet.

The technical data contained herein is based on our present knowledge and experience and we cannot be held liable for any errors, inaccuracies, omissions or editorial failings that result from technological changes or research between the date of issue of this document and the date the product is acquired. Before using the product, the user should carry out any necessary tests in order to ensure that the product is suitable for the intended application. Moreover, all users should contact the seller or the manufacturer of the product for additional technical information concerning its use if they think that the information in their possession needs to be clarified in any way, whether for normal use or a specific application of our product.

Our guarantee applies within the context of the statutory regulations and provisions in force, current professional standards and in accordance with the stipulations set out in our general sales conditions.

The information detailed in the present technical data sheet is given by way of indication and is not exhaustive. The same applies to any information provided verbally by telephone to any prospective or existing customer.