



Product code : 77004

EMFIMASTIC ACRYLIQUE PLUS

DESCRIPTION

EMFIMASTIC ACRYLIQUE PLUS is a one-component, water-based, plastic-elastic acrylic sealant, which forms a flexible and resistant joint after drying.

EMFIMASTIC ACRYLIQUE PLUS has CE marking for following application: sealant for facade elements for interior and exterior applications according to European Standard EN 15651-1 (F EXT-INT).

EMFIMASTIC ACRYLIQUE PLUS benefits from the SNJF Label on anodized aluminium and mortar without primer in class 12,5P.



ADVICE

See also material safety data sheet

AREAS OF APPLICATIONS

EMFIMASTIC ACRYLIQUE PLUS is specially adapted for finishing joints (plinths, moldings or partitions), caulking of gaps around frames, doors, panels, etc. and for the filling of fissures and cracks (4 to 25 mm width, 6 to 14 mm depth).

EMFIMASTIC ACRYLIQUE PLUS is also suitable for tightening wood, metal and synthetic joinery with brick and concrete.

EMFIMASTIC ACRYLIQUE PLUS adheres without primer on most of the commonly used building substrates like metals, ceramic tiles, hard PVC and on porous substrates like wood, stone, concrete, plaster, etc.

EMFIMASTIC ACRYLIQUE PLUS can be painted after drying.

EMFIMASTIC ACRYLIQUE PLUS is not suitable for glazing applications or sanitary joints and is not recommended on PE, PP, PTFE, glass, natural stone and bituminous surfaces.

TECHNICAL DATA

INSTRUCTIONS FOR USE

Refer to product's technical data sheet.

The technical data contained herein is based on our present knowledge and experience and we cannot be held liable for any errors, inaccuracies, omissions or editorial failings that result from technological changes or research between the date of issue of this document and the date the product is acquired.

Before using the product, the user should carry out any necessary tests in order to ensure that the product is suitable for the intended application. Moreover, all users should contact the seller or the manufacturer of the product for additional technical information concerning its use if they think that the information in their possession needs to be clarified in any way, whether for normal use or a specific application of our product.

Our guarantee applies within the context of the statutory regulations and provisions in force, current professional standards and in accordance with the stipulations set out in our general sales conditions.

The information detailed in the present technical data sheet is given by way of indication and is not exhaustive. The same applies to any information provided verbally by telephone to any prospective or existing customer.