



Product code : 77004

EMFIMASTIC ACRYLIQUE PLUS

Meets SNJF standard (class 12,5P)

DESCRIPTION

EMFIMASTIC ACRYLIQUE PLUS is a one component plastic-elastic sealant based on acrylic water dispersion, which is classified in first category according to French SNJF standard.


AREAS OF APPLICATIONS

EMFIMASTIC ACRYLIQUE PLUS can be used in the building industry for joints between wooden or metal window frames and concrete or brickwork ; windowsills, skirting boards and aerated concrete ; wall and ceiling ; stairs and walls.

EMFIMASTIC ACRYLIQUE PLUS has CE marking for following application : sealant for facade elements for interior and exterior applications according to European Standard EN 15651-1 (F EXT-INT).

EMFIMASTIC ACRYLIQUE PLUS is classified as 12.5 P according to ISO 11600 standard.

EMFIMASTIC ACRYLIQUE PLUS is unsuitable for "sanitary joints" or "glazing" applications. EMFIMASTIC ACRYLIQUE PLUS is not recommended on PE, PP, PTFE, glass, natural stone and bituminous surfaces.



ADVICE

See also material safety data sheet

TECHNICAL DATA

Appearance	Pasty
Color	White
Density at 20°C	1.62
Application temperature	5 to 40 °C
Cold resistance	Not frost resistant
Temperature resistance	- 30 to + 80 °C
Cleaner	Water before drying
Specific data	Skin time formation at 23 °C and 55 % RH : approx 30 min Hardening at 23 °C and 50 % RH : 0.5 mm/24h Joint movement capability : 12.5 % Elongation at break (ISO 8339) : > 500% Shore A hardness (ISO 868) : 12

INSTRUCTIONS FOR USE

Substrates preparation :

The substrates to be coated must be dust free and not have any traces of grease or other contaminants that could adversely affect the bonding performance.

Clean them with isopropyl alcohol or methylethylketone (MEK).

Check the compatibility of the solvent used with the substrates.

Solvents must comply with local regulations.

When using solvents, extinguish all sources of ignition and carefully follow the safety and handling instructions given by the manufacturer.

Allow the substrate to dry after degreasing.

If necessary, rub down metal surfaces beforehand. Clean them after rubbing down.

We recommend to clean concrete with a metal brush.

Use diluted EMFIMASTIC ACRYLIQUE PLUS (about 1 part of EMFIMASTIC ACRYLIQUE PLUS for 2 parts of water) as a primer for highly porous surfaces.

Adhesion tests prior to the application are recommended.

Application :

EMFIMASTIC ACRYLIQUE PLUS may be applied by a manual or pneumatic gun (in according to french SFJF recommendations to be sure to meet SNJF standard).

After application, use a wet putty knife to smooth the joint.

Do not apply at a temperature under 5 °C. In cold weather, store the cartridges at about 20 °C before use.

Cleaning :

Tools should be cleaned with water before setting of the sealant. After curing, abrasion is necessary.

CONSUMPTION

300 ml cartridge

Tube (mm)	2	3	4	5	6	7	8	9	10
Length of cord (m)	95	42	24	15	10,5	7,5	5,5	4,5	3,5

STORAGE AND SHELF LIFE

12 months in unopened original packaging stored in dry premises between 5 and 25 °C.

PACKAGING

300 mL cartridges

SAFETY

Read material safety data sheet.

PRECAUTIONS FOR USE

Application on highly filled paints may cause cracks in the paint film.

Testing is required before painting.

Outside application must not be made under rain.

Do not expose to continuous contact with water.

The technical data contained herein is based on our present knowledge and experience and we cannot be held liable for any errors, inaccuracies, omissions or editorial failings that result from technological changes or research between the date of issue of this document and the date the product is acquired. Before using the product, the user should carry out any necessary tests in order to ensure that the product is suitable for the intended application. Moreover, all users should contact the seller or the manufacturer of the product for additional technical information concerning its use if they think that the information in their possession needs to be clarified in any way, whether for normal use or a specific application of our product. Our guarantee applies within the context of the statutory regulations and provisions in force, current professional standards and in accordance with the stipulations set out in our general sales conditions. The information detailed in the present technical data sheet is given by way of indication and is not exhaustive. The same applies to any information provided verbally by telephone to any prospective or existing customer.