



Product code : 77006

EMFIMASTIC ACRYL-PARQUET

DESCRIPTION

EMFIMASTIC ACRYL-PARQUET is a high-quality, fast curing and easy to apply acrylic sealant for parquet and laminate.

EMFIMASTIC ACRYL-PARQUET is available in different wood colors.



AREAS OF APPLICATIONS

EMFIMASTIC ACRYL-PARQUET is specially adapted for finishing joints or caulking of gaps between all types of parquet, wood and wood species (as well as on laminated floors) and walls or skirting boards.

EMFIMASTIC ACRYL-PARQUET adheres perfectly on most of the commonly used building substrates and porous surfaces: wood, stone, concrete, plaster, metal, ceramic tiles, hard PVC and laminate flooring.

It is however recommended to perform preliminary tests to determine whether a surface preparation is necessary.

EMFIMASTIC ACRYL-PARQUET can be painted after drying.

Not suitable for vinyl (PVC, LVT) and linoleum or for glazing applications or sanitary joints.

EMFIMASTIC ACRYL-PARQUET is not recommended on PE, PP, PTFE, glass, natural stone and bituminous surfaces.

ADVICE

See also material safety data sheet

TECHNICAL DATA

INSTRUCTIONS FOR USE

Refer to product's technical data sheet.

The technical data contained herein is based on our present knowledge and experience and we cannot be held liable for any errors, inaccuracies, omissions or editorial failings that result from technological changes or research between the date of issue of this document and the date the product is acquired.

Before using the product, the user should carry out any necessary tests in order to ensure that the product is suitable for the intended application. Moreover, all users should contact the seller or the manufacturer of the product for additional technical information concerning its use if they think that the information in their possession needs to be clarified in any way, whether for normal use or a specific application of our product.

Our guarantee applies within the context of the statutory regulations and provisions in force, current professional standards and in accordance with the stipulations set out in our general sales conditions.

The information detailed in the present technical data sheet is given by way of indication and is not exhaustive. The same applies to any information provided verbally by telephone to any prospective or existing customer.