



Product code : 7B003L

## EMFIMASTIC CONSTRUCTION T


### DESCRIPTION

EMFIMASTIC CONSTRUCTION T is a neutral one-component alkoxy silicone sealant which cures under the effect of atmospheric moisture to form a flexible and resistant joint. It shows a high resistance to weathering and extreme temperatures.

EMFIMASTIC CONSTRUCTION T benefits from the SNJF Label without primer on anodized aluminium and on mortar in class F 25E.

It has CE marking for following applications:

- sealant for facade elements for interior and exterior applications according to European Standard EN 15651-1 (F EXT-INT).
- sealant for glazing according to European Standard EN 15651-2 (G).



### ADVICE

See also material safety data sheet

### AREAS OF APPLICATIONS

EMFIMASTIC CONSTRUCTION T is specially adapted for jointing applications in different domains like light and heavy prefabricated building, carpentry (wood, aluminium, PVC, curtain walls), glazing, expansion joints in traditional building, as well as joints in the industry.

Very easy to apply and odorless, EMFIMASTIC CONSTRUCTION T adheres without primer on substrates commonly used in the building industry, like glass, aluminium, reinforced concrete, ABS, high impact polystyrene, brass, bronze, steel, stainless or galvanized steel, tiles, wood, PVC, etc.

If applied on concrete, brick or cement, the use of a primer is recommended (contact our technical department if needed).

EMFIMASTIC CONSTRUCTION T is not paintable after curing.

EMFIMASTIC CONSTRUCTION T is not suitable for applications with permanent water contact, sanitary applications or mirror bonding and is not recommended on PE, PP, PTFE, natural stone, bituminous surfaces, polyacrylate and polycarbonate.

### TECHNICAL DATA

### INSTRUCTIONS FOR USE

Refer to product's technical data sheet.

The technical data contained herein is based on our present knowledge and experience and we cannot be held liable for any errors, inaccuracies, omissions or editorial failings that result from technological changes or research between the date of issue of this document and the date the product is acquired.

Before using the product, the user should carry out any necessary tests in order to ensure that the product is suitable for the intended application. Moreover, all users should contact the seller or the manufacturer of the product for additional technical information concerning its use if they think that the information

in their possession needs to be clarified in any way, whether for normal use or a specific application of our product.

Our guarantee applies within the context of the statutory regulations and provisions in force, current professional standards and in accordance with the stipulations set out in our general sales conditions.

The information detailed in the present technical data sheet is given by way of indication and is not exhaustive. The same applies to any information provided verbally by telephone to any prospective or existing customer.